

MICROFILTERED WATER DISTRIBUTOR

CHILLER

Compact chiller for quick and easy extraction
 Ecological cooling gas R290
 Room Temperature +10°C | +45°C
 Water production: 80 Ltr/h
 Water output temperature: +3°C | +10°C
 Ice bank: 4Kg - Cooling system: Ice bank

LIGHTING

LED

GRAPHIC DISPLAY

Programmable in different languages with various publicity spot options. Programmable stand-by
 Optional: Display touch 7"

HYGIENE DEVICES (optional)

UV-C lamp to eliminate bacteria from the water
 Sanitizing of the spout and retrieval area by ozone jet or 165 °C steam jet

TECHNOLOGY

Telemetry;
 applicable internet Modem;
 EVA-DTS, GPE DATA (software updating by PC)

PAYMENT SYSTEM

Executive – MDB
 predisposed for latest generation payment systems (credit card, Paypal,...)

THE CONSUMER CAN

Fill their own 0,5 ltr container (bottle/flask...)
 Choose by keypad the type of water preferred: still, sparkling, slightly sparkling.
 Choose by keypad the temperature of the water: room temperature, cool, cold



DIMENSIONS

HEIGHT	183 cm
WIDTH	65,5 cm
DEPTH	72 cm
WEIGHT	140 kg

ELECTRIC POWER SUPPLY ABSORBED POWER

Compressor: 1/6 Hp
 Chiller group absorption: 0,35Kw
 Total absorption: 0,45Kw
 210-240Vac/50Hz

Average annual consumption: 160KWh
 With optional UV lamp: + 18 KWh